



**1900mm**  
Print Width

**i3200-A1**  
PrintHead Type

## Technical Parameters

Model	<b>GFX-DS-E15-1.1</b>	
Print Head	<b>Epson® i3200-A1</b>	
Number of Print Head	<b>15</b>	
Printing Resolution	<b>360x1200 dpi</b>	<b>360x1200 dpi</b>
Print Pass	<b>1 Pass</b>	<b>2 Pass</b>
Speed (m <sup>2</sup> /h)**	<b>350 m<sup>2</sup>/h</b>	<b>200 m<sup>2</sup>/h</b>
Colors	<b>4 Color (CMYK)</b>	
Ink Type	<b>Dye Sublimation / Aqueous based Pigmented Inks</b>	
Maximum Print Width	<b>Upto 1900 mm</b>	
Data Transmission Interface	<b>HI-USB 3.0 / LAN</b>	
RIP Software	<b>Maintop 6.1, Photoprint / NeoStampa</b>	
Media	<b>Sublimation Paper</b>	
Ink Capacity	<b>10 Litre per Colour</b>	
Power Parameter	<b>AC 220 V, 15 kw</b>	
Feeding System	<b>Industrial Auto Feeding System with Airshaft &amp; Drive System</b>	
Take-UP System	<b>Industrial Auto Take-Up System with Airshaft &amp; Drive System</b>	
Environmental Requirements	<b>Temperature : 20-30°C   Humidity : 45% - 60%</b>	
Add-ons***	<b>NA</b>	
Loading Roll Capacity	<b>3000m / 30gsm (Optional 10000m)</b>	
Net Weight	<b>900kg(Approx)</b>	
Dimension (L x W x H)****	<b>3600(L)mm x 1300(W)mm x 1850(H)mm</b>	
Carriage System	<b>Belt System / Magnetic Linear Rail (Optional)</b>	

\* All trademarks mentioned are the property of their respective owners and have been mentioned herein for reference purpose only.

\*\* Maximum speed shown, speed will vary based on size of substrate, carriage speed, number of passes, feather conditions, machine maintenance and other factors.

\*\*\* May be available at additional cost.

\*\*\*\* Actual dimensions may vary slightly.