



**3200mm**  
Print Width

**i3200-A1**  
PrintHead Type

## Technical Parameters

Model	<b>GFX-DS-E8-1.2</b>	
Print Head	<b>Epson* i3200-A1</b>	
Number of Print Head	<b>8</b>	
Printing Resolution	<b>360x1200 dpi</b>	<b>360x2400 dpi</b>
Print Pass	<b>1 Pass High Speed</b>	<b>2 Pass High Speed</b>
Speed (m <sup>2</sup> /h)**	<b>250 m<sup>2</sup>/h</b>	<b>140 m<sup>2</sup>/h</b>
Colors	<b>4/8 Color (CMYK+4)</b>	
Ink Type	<b>Dye Sublimation Inks</b>	
Maximum Print Width	<b>3.2 meters</b>	
Data Transmission Interface	<b>HI-USB 3.0</b>	
RIP Software	<b>Maintop 6.1, Photoprint / NeoStampa</b>	
Media	<b>Sublimation Paper</b>	
Ink Capacity	<b>10 Litre per Colour</b>	
Power Parameter	<b>AC 220 V, 60A/ 24.1 kW</b>	
Feeding System	<b>Industrial Auto Feeding System with Airshaft &amp; Drive System</b>	
Take-UP System	<b>Industrial Auto Take-Up System with Airshaft &amp; Drive System</b>	
Environmental Requirements	<b>Temperature : 20-30°C   Humidity : 45% - 65%</b>	
Add-ons***	<b>NA</b>	
Loading Roll Capacity	<b>1000m / 30gsm</b>	
Net Weight	<b>800kg(Approx)</b>	
Dimension (L x W x H)****	<b>4840(L)mm x 1460(W)mm x 1550(H)mm</b>	
Carriage System	<b>Belt System</b>	

\* All trademarks mentioned are the property of their respective owners and have been mentioned herein for reference purpose only.

\*\* Maximum speed shown, speed will vary based on size of substrate, carriage speed, number of passes, feather conditions, machine maintenance and other factors.

\*\*\* May be available at additional cost.

\*\*\*\* Actual dimensions may vary slightly.