



### Technical Parameters

Model	GFX-DS-E16-2.1	
Print Head	Epson® i3200-A1	
Number of Print Head	16	
Printing Resolution	360x1200dpi	720x1200dpi
Print Pass	1 Pass	2 Pass
Speed (m <sup>2</sup> /h)**	600 mtr.	300 mtr.
Colors	4 Color (CMYK)	
Ink Type	Dye Sublimation / Aqueous based Pigmented Inks	
Maximum Print Width	Upto 1950 mm	
Data Transmission Interface	USB 3.1	
RIP Software	Onyx / NeoStampa	
Media	Sublimation Paper	
Ink Capacity	10 Litre Refillable tank	
Power Parameter	AC 220 V, 43 A, 50/60 Hz	
Feeding System	Industrial Auto Feeding System with Airshaft & Drive System	
Take-UP System	Industrial Auto Take-Up System with Airshaft & Drive System	
Environmental Requirements	Temperature : 18-24°C	
Add-ons***	Heavy Feeding System, Intelligent Drying System	
Loading Roll Capacity	10000m / 35gsm	
Net Weight	1550kg(Approx)	
Dimension (L x W x H)****	2342(L)mm x 5020(W)mm x 1975(H)mm	
Carriage System	Magnetic Linear Rail	

\* All trademarks mentioned are the property of their respective owners and have been mentioned herein for reference purpose only.

\*\* Maximum speed shown, speed will vary based on size of substrate, carriage speed, number of passes, feather conditions, machine maintenance and other factors.

\*\*\* May be available at additional cost

\*\*\*\* Actual dimensions may vary slightly.