

Digital Textile Printer 16H Epson* i3200 (Dye-Sublimation)



Technical Parameters

Model	GFX-DS-E16-3.1	
Print Head	Epson i3200	
Number of Print Head	16	
Printing Resolution	360x1200 dpi	720x1200 dpi
Print Pass	1 Pass	2 Pass
Speed (m²/h)**	450 m²/h	230 m²/h
Colors	4 Color (CMYK)	
Ink Type	Dye Sublimation / Aqueous based Pigmented Inks	
Maximum Print Width	Upto 1778 mm	
Data Transmission Interface	HI-USB 3.0 / LAN	
RIP Software	NeoStampa	
Media	Sublimation Paper	
Ink Capacity	10 Litre per Colour	
Power Parameter	AC 220 V, 50/160 Hz	
Feeding System	Industrial Auto Feeding System with Airshaft & Drive System	
Take-UP System	Industrial Auto Take-Up System with Airshaft & Drive System	
Environmental Requirements	Temperature: 18-24°C	
Add-ons***	NA	
Loading Roll Capacity	3000m / 31gsm	
Net Weight	1600kg(Approx)	
Dimension (L x W x H)****	2940(L)mm x 850(W)mm x 1550(H)mm	
Carriage System	Magnetic Linear Rail	

All trademarks mentioned are the property of their respective owners and have been mentioned herein for reference purpose only.

^{**} Maximum speed shown, speed will vary based on size of substrate, carriage speed, number of passes, feather conditions, machine maintenance and other factors.

*** May be available at additional cost.

**** Actual dimensions may vary slightly.