



### Technical Parameters

Model	GFX-DS-E24-1.1	
Print Head	Epson® i3200 - A1	
Number of Print Head	24	
Printing Resolution	360x1200 dpi	360x1200 dpi
Print Pass	1 Pass	2 Pass
Speed (m <sup>2</sup> /h)**	900 m <sup>2</sup> /h	450 m <sup>2</sup> /h
Colors	4 Color (CMYK)	
Ink Type	Dye Sublimation / Aqueous based Pigmented Inks	
Maximum Print Width	Upto 1900 mm	
Data Transmission Interface	HI-USB 3.0 / LAN	
RIP Software	Maintop 6.1, Photoprint / NeoStampa	
Media	Sublimation Paper	
Ink Capacity	10 Litre per Colour	
Power Parameter	AC 220 V, 50/60 Hz 29 kw	
Feeding System	Industrial Auto Feeding System with Airshaft & Drive System	
Take-UP System	Industrial Auto Take-Up System with Airshaft & Drive System	
Environmental Requirements	Temperature : 18-24°C	
Add-ons***	NA	
Loading Roll Capacity	3000m / 30gsm (Optional 10000m)	
Net Weight	2200kg(Approx)	
Dimension (L x W x H)****	4225(L)mm x 1450(W)mm x 1950(H)mm	
Carriage System	Magnetic Linear Rail	

\* All trademarks mentioned are the property of their respective owners and have been mentioned herein for reference purpose only.

\*\* Maximum speed shown, speed will vary based on size of substrate, carriage speed, number of passes, feather conditions, machine maintenance and other factors.

\*\*\* May be available at additional cost

\*\*\*\* Actual dimensions may vary slightly.