


Technical Parameters

Model	GFX-RE-RG616-1.1
Print Head	Ricoh* Gen6
Number of Print Head	16
Control System	BYHX
Printing Width	2 meter
Colors	4/8 Color
Speed (m ² /h)**	2 Pass (508x600dpi): 240m ² /h 3 Pass (508x900dpi): 160m ² /h
Ink Type	Reactive/Disperse/Pigment
Media Conveyor	Conveyor Belt
Carriage	Auto. Lifting(3-30mm adjustable)
Media Height	3-5mm
Carriage Scanning	High Precision Magnetic Linear RailerSystem
Ink Supply	Negative Pressure Ink Delivery System
Feeding System	Inflatable Shaft + Tension Bar
Water Unit	Sponge + Scraper + Brush + Towel roller
Print Media	Pure Cotton & Viscose
RIP Software	NeoStampa
Data Transmission	USB 3.0
Power	Printer - 8 kW Dryer - 30 kW
Net Weight	3500kg(Approx)
Dimension (L x W x H)***	Printer - 4830(L)mm x 2737(W)mm x 1895(H)mm Dryer - 2300(L)mm x 1765(W)mm x 1080(H)mm
Carriage System	Magnetic Linear Rail



Ricoh G6 Print Head



Carriage Auto Up-Down Motor



Dual-Level Ink Box with Electromagnetic Valve



High-Precision Magnetic Grid



Degassing Module



Belt Cleaning Device



Conveyor Belt



Negative Pressure Ink System



Magnetic Linear Rail System



Multi-Roller Feeding System

* All trademarks mentioned are the property of their respective owners and have been mentioned herein for reference purpose only.

** Maximum speed shown, speed will vary based on size of substrate, carriage speed, number of passes, feather conditions, machine maintenance and other factors.

*** Actual dimensions may vary slightly.